

Terminal Punto de Ventas PARTNER TECH AUDREY

01

sistema Operativo

windows 10/11
Android (Opcional)

02

MicroProcesador

Intel®Core™i3-1215U
Intel®Core™i5-1245U

03

Memoria ROM

4 GB de ROM, DDR4, hasta 8 GB
- 16 GB - 32 GB

04

Disco Duro

128 GB de RAM, hasta 512 GB
SSD

04

Pantalla táctil

Pantalla retroiluminada
LED de 17 pulgadas

04

WIFI

IEEE 802.11 a/b/g/n/ac,
2,4 GHz (opción de 5,0 GHz)

05

Segunda Pantalla

9,7 Pulgadas y
15 Pulgadas (Opcional las dos)



Terminal Punto de Ventas PARTNER TECH AUDREY

Specifications



| | A4-1-AL | A4-1-E |
|------------------------|--|--|
| Size | 15" | |
| Aspect Ratio | 4:3 | |
| Resolution | 1024 x 768 | |
| Brightness | 400 nits | |
| Touch | PCAP Touch | |
| CPU | Alder Lake-P Intel® Core™ i3-1215U Intel® Core™ i5-1245U, vPro Intel® Core™ i7-1265U, vPro | Elkhart Lake Intel® Celeron® J6412 |
| Memory | DDR4 4GB, 8GB, 16GB, 32GB | |
| Storage | M.2 PCIe SSD: 128GB / 256GB / 512GB | |
| I/O Interface | 3 x serial ports, RS-232 (RJ45), 0V/5V/12V selected in BIOS (COM1, COM2, COM3) 1 x Intel LAN (IEEE 802.3 10/100/1000 Mbps) 1 x RJ11 port support for 2 cash drawers with 24V / 12V jumper setting 1 x DC +12V out 4 x USB 3.2 + 2 x USB 2.0 1 x DC +12V input 1 x audio (1 x line-out) 1 x HDMI 1 x Type-C (data transfer + display) | |
| Speaker | 1 x speaker (3W) | |
| Peripheral Options | MSR, fingerprint reader, RFID/NFC, i-Button, VFD, USB 2nd display, HDMI 2nd display, 2D bar code scanner, camera, IO extension box (EX-100, EX-101, EX-300), PS-103 Cosmo printer stand (space-saving stand, compatible with RP-700 or Epson TM-T70 II) | |
| Wireless Option | Wi-Fi 6E Intel AX210 IEEE 802.11 a/b/g/n/ac/axR2/axR2, BT 5.2 | |
| Display Support | 3 independent displays (Main Display + HDMI + Type-C) | |
| Spill & Dust Resistant | Front panel IP65, whole unit IP54 certified | |
| Operating System | 1. Windows 11 IoT Enterprise GAC (64bit) ready 2. Windows 10 IoT Enterprise LTSC 21H2 (64bit) 3. Linux Ubuntu 22.04 | |
| TPM & vPro | 1. Intel vPro (i5/i7 CPU only) 2. S/W TPM 2.0 (BIOS) | S/W TPM 2.0 (BIOS) |
| Power Adaptor | AC-In 100~240V / DC-Out 12V, 90W | AC-In 100~240V / DC-Out 12V, 65W / 90W |
| Reliability | System operating temperature: 0~40°C / 32~104°F System humidity: 15% ~ 80% Storage temperature: -20~60°C / -4~140°F | |
| Dimensions (Wx Hx D) | 360 x 350 x 201 mm / 14.17 x 13.77 x 7.87 in | |
| Weight | 6.2 kg / 13.67 lb | |

*Specification is subject to change without prior notice

Audrey

PARTNER